



No other playground surfacing material offers the degree of safety assurance that rubber tiles can provide. Ultimate RB Bounce Back Safety Surface is a shock absorbing, resilient rubber tile that provides long-term answers to playground safety and features ADA accessibility.

BOUNCE BACK BENEFITS

RECYCLED RUBBER	COLOR OPTIONS	ADA COMPLIANT
WEATHER & SLIP RESISTANT	MOISTURE PERMEABILITY	EXCELLENT DRAINAGE
INTERLOCKING OPTIONS	INSTALLATION EASE	QUALITY/WARRANTY
DESIGN FLEXIBILITY	MAINTENANCE EASE	IPEMA CERTIFIED

Each year over 200,000 children are injured on playgrounds in the United States. Many of these injuries result from children falling onto inadequate surfacing. Ultimate RB Bounce Back Playground Tiles offer a solution to this problem in a durable and attractive rubber tile product.

Bounce Back Tiles are designed to meet federally mandated Critical Fall Height requirements for playground equipment up to 10 feet tall. Our tiles have been certified to comply with these requirements by IPEMA through TUV/SUD, a third party independent testing/certification laboratory. Additionally, Ultimate RB conducts regular in house Critical Fall Height testing on our own certified test equipment as part of our Quality Control plan.

Wood and rubber mulch products are easily displaced, resulting in inadequate thickness/protection in large areas of the playground. They also present an undesirable and dangerous opportunity for children to swallow, throw, or kick the material. Poured-in-Place products can only be installed in specific weather conditions which limits the window for installation. Ultimate RB's factory-produced tiles eliminate these problems and offer the assurance of safe surfacing for children's play areas.



BOUNCE BACK SPECIFICATIONS



TYPICAL PROPERTIES

TILE SIZES

Interlocking 24" X 24"

THICKNESS

Standard:

- 1.75" (3' FALL PROTECTION)
- 2.25" (4' FALL PROTECTION)
- 2.5" (6' FALL PROTECTION)
- 3.5" (8' FALL PROTECTION)
- 4" (10' FALL PROTECTION)

BLACK SBR GRANULATE

0.5 IN (12.7MM)

BINDER

URETHANE

HEAVY METAL

ASTM F-963-7 PASS

MEETS ALL CPSC REQUIREMENTS




TILE SPECIFICATIONS


TEST TYPE	ASTM	RESULT
WATER PERMEABILITY	-----	.27 GAL/MIN/SQ. YD.
LEAD CONTENT	D-4004	5.97 PPM
ABRASION RESISTANCE	D-4060	WEAR INDEX 657 AVG - DURABILITY
TEAR STRENGTH	D-624	124 LBF/IN & PSI AVG - DURABILITY
DUAL DUROMETER	-----	25/45 - RESITANCE
WEATHERIZATION	C67/D573	NO FAIL AFTER FREEZE/THAW/DRY
FALL HEIGHT	F-1292-99	MET CRITERIA
COEFFICIENT OF FRICTION	D-1028	.65 DRY/.63 WET

The values shown represent independent and production laboratory taken tests for the 24"x24" cushions, which may vary slightly by color or when field tested.


STANDARD COLORS



ALPINE MEADOW GREEN




STREAMSIDE BLUE



SANDY BEACH TAN



RAINFORREST GREEN



CRATER LAKE BLUE




HAZELNUT BROWN



DENIM BLUE



CAYENNE RED



CASCADE GREEN



BLACK

WARRANTY

Ultimate RB Bounce Back Playground Tiles carry a 10-year limited warranty for defects in material.

Create your own
Ultimate RB color



WWW.ULTIMATERB.COM

blend with our online
CUSTOM COLOR TOOL!

Made From Recycled Rubber!

CALL TODAY
FOR A CUSTOM QUOTE!



1430 North Main St.
Delphos, OH 45833
T. 419.692.3005

904 NE 10th Ave.
McMinnville, OR 97128
T. 503.472.4691



© 2016 Ultimate RB
All rights reserved
www.UltimateRB.com