



*Ultimate RB Rolled Rubber flooring provides a durable, resilient surface for dog play, agility practice, and competition, while also allowing for easy cleaning and maintenance.*

**ULTIMATE RB ROLLED RUBBER BENEFITS**

ENVIRONMENTALLY FRIENDLY	AESTHETIC	ISO 9001
DURABLE	ANTI-FATIGUE RESILIENCE	MINIMAL ODOR
SHOCK & SOUND ABSORBING	EASY TO CLEAN	CUSTOM SIZING & COLORS
VERSATILE	AMERICAN MADE	EASY INSTALLATION

Ultimate RB Rubber flooring provides a durable, resilient surface for dog play, agility practice, and competition, while also allowing for easy cleaning and maintenance. The anti-fatigue qualities of the soft rolled rubber material reduce stress on the joints and muscles of pets and their human caretakers, and the superior traction of rubber flooring is unequalled. From doggy daycare facilities to canine agility courses, rolled rubber is an ideal flooring material.

**STANDARD PRODUCTS**

Ultimate RB maintains a substantial inventory of many standard rolled rubber products in thicknesses including 8 mm and 9.5 mm. These standard rolls are 4' x 25' and 4' x 50'. In addition to black, our inventory of standard products includes rolls in Grey, Blue, Red, Green, Blue/Gray, and Cocoa/Eggshell. The color concentration of the standard rolls is 20%.

**COLORS**

Ultimate RB also maintains an inventory of highly colored flooring material that can be cut to your specifications for quick turnaround.



## FLOORING SPECIFICATIONS



### TYPICAL PROPERTIES

**\*WIDTH**  
Standard: 4' (1.2M)

**\*THICKNESS**  
Standard:  
3.4MM (.134"), 4MM (.157"), 6MM (.236"), 8MM (.300"), 9MM (.354"),  
9.5MM (.375")

**\*LENGTH**  
Standard: 25' (7.62M) & 50' (15.24M)

**COLORED EPDM GRANULATE**  
0.0394" (1MM) TO .1181" (3MM)

**BINDER**  
URETHANE

**\* CUSTOM AVAILABLE**  
**\* 3' (.91M) AVAILABLE AS CUSTOM WIDTH**





**NOTE:**  
Physical properties can vary by product type.  
Information above applies to this product only.



### ROLLED RUBBER SPECIFICATIONS

TEST TYPE	ASTM	RESULT
SHORE HARDNESS	D-2240	60 +/- 5
DENSITY	D-792	80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	300%
TENSILE STRENGTH	D-412	
TABER ABRASION	D-3884	200 PSI
FLAME SPREAD	E-84	2.34
SMOKE DENSITY	E-84	65
COMPRESSION SET	D-395	< 450
VOC EMISSIONS	D-5116	9.7%
RESISTANCE TO CHEMICALS	F-925-02	0.5 MG/M <sup>2</sup> OR LESS
STATIC LOAD LIMIT	F-970	NO CHANGE
ELECTROSTATIC PROPENSITY	AATCC 134-1996	-0.001 IN
CRITICAL RADIANT FLUX	E-648 0.52	NEG 0.6 KV W/CM2

## STANDARD COLORS



## MAINTENANCE & FLOOR CARE

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit [www.UltimateRB.com](http://www.UltimateRB.com)

## WARRANTY

Ultimate RB Rolled Rubber products carry a 5-year limited warranty for defects in material and workmanship.

Create your own  
Ultimate RB color



blend with our online  
**CUSTOM COLOR TOOL!**

Made From Recycled Rubber!

**CALL TODAY**  
FOR A CUSTOM QUOTE!



1430 North Main St.  
Delphos, OH 45833  
T. 419.692.3005

904 NE 10th Ave.  
McMinnville, OR 97128  
T. 503.472.4691



© 2016 Ultimate RB  
All rights reserved  
[www.UltimateRB.com](http://www.UltimateRB.com)