



Ultimate Design recycled rubber flooring is an ideal choice for the varying demands of the commercial market.

- *Environmentally Friendly*
- *Durable*
- *Shock & Sound Absorbing*
- *Anti-Fatigue*
- *Easy to Clean*
- *Made in USA*
- *ISO 9001*
- *FloorScore Certified*
- *Custom Sizing & Colors*
- *Easy Installation*
- *Comes in Roll & Tile Options*

ULTIMATE DESIGN ROLLED RUBBER AND TILES ARE GREAT FOR

- | | |
|--------------------------------------|------------------------------|
| RETAIL SPACES, OFFICES & RESTAURANTS | SPORTS FACILITIES AND ARENAS |
| POOLSIDE WALKWAYS | HEALTH & FITNESS CENTERS |
| HOSPITALS, SCHOOLS & LIBRARIES | GOLF & SKI RESORTS |
| AEROBIC FITNESS & YOGA STUDIOS | HOSPITALITY AREAS |

Admired by architects and designers. Recommended and selected by specifiers. Preferred by green building managers. Ultimate Design recycled rubber flooring has proven to be the floor of choice by those who desire sustainable, environmentally friendly, resilient flooring. Ultimate Design is available in an infinite number of colors and design options. Manufactured from vivid EPDM color granules - which consist of 28% post-industrial recycle - Ultimate Design rubber flooring can be blended to match your custom color palette, achieving virtually any color range for an unlimited number of applications. Schools, hospitals, retail spaces and corporate office buildings are common installations. Ultimate Design is FloorScore certified and meets the CHPS criteria for strict indoor air quality standards. In addition, Ultimate Design can contribute to multiple LEED credits under the U.S. Green Building Council's rating system.

COLORS

Ultimate RB also maintains an inventory of highly colored flooring material that can be cut to your specifications.



FLOORING SPECIFICATIONS



TYPICAL PROPERTIES - ROLLS

***WIDTH**
Standard: 4'

***THICKNESS**
Standard:
3.4MM (.134"), 4MM (.157"), 6MM (.236"),
8MM (.300"), 9MM (.354"), 9.5MM (.375")

***LENGTH**
Standard: 25' (7.62M) & 50' (15.24M)

COLORED EPDM GRANULATE
0.0394" (1MM) TO 0.1181" (3MM)

BINDER
URETHANE

***CUSTOM AVAILABLE**
*** 3' (.91M) AVAILABLE AS CUSTOM WIDTH**

NOTE:
Physical properties can vary by product type. Information above applies to this product only.



TYPICAL PROPERTIES - TILES

TILE SIZES
Interlocking
18" X 18" (0.4572M²) +/- 0.078"
24" X 24" (0.61M²) +/- 0.078"
36" X 36" (0.91M²) +/- 0.078"
48" X 48" (1.2192M²) +/- 0.078"

Square
24" X 24" (0.61M X 0.61M)
36" X 36" (0.91M X 0.91M)
36" X 36" (0.91M²) +/- 0.078"
48" X 48" (1.2192M²) +/- 0.078"

***THICKNESS**
Standard: 3.4MM (.134"), 4MM (.157"),
6MM (.236"), 8MM (.300"), 9MM (.354"),
9.5MM (.375")

TOLERANCE
+/- 0.020"

COLORED EPDM GRANULATE
0.0394" (1MM) TO 0.1181" (3MM)

BINDER
URETHANE

***CUSTOM AVAILABLE.**



ULTIMATE DESIGN SPECIFICATIONS

TEST TYPE	ASTM	RESULT
SHORE HARDNESS	D-2240	60 +/- 5
DENSITY	D-792	80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	300%
TENSILE STRENGTH	D-412	200 PSI
TABER ABRASION	D-3884	2.34
COMPRESSION SET	D-395	9.7%
VOC EMISSIONS	D-5116	0.5 MG/M ² OR LESS
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	-0.001 IN
ELECTROSTATIC PROPENSITY	AATCC 134-1996	NEG 0.6 KV
CRITICAL RADIANT FLUX	E-648 0.52	W/CM2

MAINTENANCE & FLOOR CARE

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com

WARRANTY

Ultimate RB Rolled Rubber products carry a 1-year limited warranty for defects in material and workmanship.

Create your own
Ultimate RB color



WWW.ULTIMATERB.COM

blend with our online
CUSTOM COLOR TOOL!

Made From Recycled Rubber!

CALL TODAY
FOR A CUSTOM QUOTE!



1430 North Main St.
Delphos, OH 45833
T. 419.692.3005

904 NE 10th Ave.
McMinnville, OR 97128
T. 503.472.4691



© 2016 Ultimate RB
All rights reserved
www.UltimateRB.com