

Popular in health and fitness clubs, weight rooms and ice rinks, Ultimate RB Rolled Rubber flooring is a champion in a wide variety of applications.

- *Environmentally Friendly*
- *Durable*
- *Shock & Sound Absorbing*
- *Anti-Fatigue*
- *Easy to Clean*
- *Made in USA*
- *ISO 9001*
- *Custom Sizing & Colors*
- *Easy Installation*
- *FloorScore Certified*

ULTIMATE RB ROLLED RUBBER IS GREAT FOR

- | | |
|--------------------------------------|------------------------------|
| RETAIL SPACES, OFFICES & RESTAURANTS | SPORTS FACILITIES AND ARENAS |
| POOLSIDE WALKWAYS | HEALTH & FITNESS CENTERS |
| HOSPITALS, SCHOOLS & LIBRARIES | GOLF & SKI RESORTS |
| AEROBIC FITNESS & YOGA STUDIOS | WEIGHT & LOCKER ROOMS |

Our rolled rubber offers superior durability and is suitable for indoor applications that require resilience, sound absorption, spike resistance, and traction. Ultimate RB Rolled Rubber features a dense rubber construction that provides excellent high impact durability and superior slip resistance in wet or dry conditions. The product also combines anti-fatigue and ergonomic comfort properties with very low maintenance. Containing up to 92% recycled rubber, Ultimate RB Rolled Rubber is widely regarded as the premiere “green” resilient flooring choice.

STANDARD PRODUCTS

Ultimate RB manufactures standard rolled rubber products in thicknesses including 8 MM and 9.5 MM. These standard rolls are 4’ x 25’ and 4’ x 50’. In addition to black, our inventory of standard products includes rolls in Grey, Blue, Red, Green, Blue/Grey, and Cocoa/Eggshell. The color concentration of the standard rolls is 20%.



FLOORING SPECIFICATIONS



TYPICAL PROPERTIES

***WIDTH**
Standard: 4'

***THICKNESS**
Standard:
3.4MM (.134"), 4MM (.157"), 6MM (.236"), 8MM (.300"), 9MM (.354"),
9.5MM (.375")

***LENGTH**
Standard: 25' (7.62M) & 50' (15.24M)

COLORED EPDM GRANULATE
0.0394" (1MM) TO .1181" (3MM)

BINDER
URETHANE

***CUSTOM AVAILABLE**
***3' (.91M) AVAILABLE AS CUSTOM WIDTH**



NOTE:
Physical properties can vary by product type.
Information above applies to this product only.



ROLL SPECIFICATIONS

TEST TYPE	ASTM	RESULT
SHORE HARDNESS	D-2240	60 +/- 5
DENSITY	D-792	80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	300%
TENSILE STRENGTH	D-412	
TABER ABRASION	D-3884	200 PSI
FLAME SPREAD	E-84	2.34
SMOKE DENSITY	E-84	65
COMPRESSION SET	D-395	< 450
VOC EMISSIONS	D-5116	9.7%
RESISTANCE TO CHEMICALS	F-925-02	0.5 MG/M ² OR LESS
STATIC LOAD LIMIT	F-970	NO CHANGE
ELECTROSTATIC PROPENSITY	AATCC 134-1996	-0.001 IN
CRITICAL RADIANT FLUX	E-648 0.52	NEG 0.6 KV W/CM2

STANDARD COLORS



MAINTENANCE & FLOOR CARE

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com

WARRANTY

Ultimate RB Rolled Rubber products carry a 5-year limited warranty for defects in material and workmanship.

Create your own
Ultimate RB color



blend with our online
CUSTOM COLOR TOOL!

Made From Recycled Rubber!

CALL TODAY
FOR A CUSTOM QUOTE!



1430 North Main St.
Delphos, OH 45833
T. 419.692.3005

904 NE 10th Ave.
McMinnville, OR 97128
T. 503.472.4691



© 2016 Ultimate RB
All rights reserved
www.UltimateRB.com