

Popular in health and fitness clubs, weight rooms, and ice rinks, Ultimate Tough recycled rubber flooring is a champion in a wide variety of applications.

- High Impact Durability
- Manufactured in the USA
- Premium Recycled Rubber
- Slip and Impact Resistant
- Easy to Clean
- Environmentally Friendly
- Customizable
- Shock and Sound Absorbing
- FloorScore Certified



ULTIMATE TOUGH ROLLS & TILES ARE GREAT FOR

WEIGHT ROOMS & GYMS	SCHOOL CAFETERIAS	SKI & SNOWBOARD SHOPS
MULTI-PURPOSE ROOMS	CONCESSION AREAS	HOME GYM FLOORING
WORK AREAS	ICE RINK WALKWAYS	STATIONARY BIKE MATTING
JUNGLE GYM & PLAY AREAS	FACTORY FLOORS	LOCKER ROOMS

ULTIMATE TOUGH PRODUCTS

Available in rolls or tiles, Ultimate Tough is ideal for high-wear and high-impact spaces that require maximum subfloor protection. Home gyms, weight rooms, and basements all benefit from durable rubber tile. It is manufactured from post-consumer recycled rubber buffings with small percentages colored EPDM. Ultimate Tough is the recommended choice for high-traffic active spaces. It provides excellent high-impact durability and superior slip resistance in wet or dry conditions. Ultimate Tough also combines anti-fatigue and ergonomic comfort properties with very low maintenance. Containing up to 92% recycled content range and low VOC emissions, Ultimate Tough is widely regarded as the premier “green” resilient flooring choice. It is available in rolls and interlocking and square tiles, and comes in 7 standard colors in variable thicknesses. Custom colors are also available.

Made From Recycled Rubber!

CALL TODAY
FOR A CUSTOM QUOTE!

ULTIMATE TOUGH SPECIFICATIONS



INTERLOCKING TILE DIMENSIONS

TILE SIZES

Interlocking

18" X 18" (0.4572M²) +/- 0.078"

24" X 24" (0.61M²) +/- 0.078"

36" X 36" (0.91M²) +/- 0.078"

48" X 48" (1.2192M²) +/- 0.078"

Square

18" X 18" (0.4572M²) +/- 0.078"

24" X 24" (0.61M²) +/- 0.078"

36" X 36" (0.91M²) +/- 0.078"

48" X 48" (1.2192M²) +/- 0.078"

*THICKNESS

Standard:

.134" (3.4MM) TO .472" (12MM)

TOLERANCE

+/- 0.020"

COLORED EPDM GRANULATE

0.0394" (1MM) TO 0.1181" (3MM)

BINDER

URETHANE

*CUSTOM AVAILABLE.



ROLL DIMENSIONS

*WIDTH

Standard:

4 FT. (1.22M)

WIDTH TOLERANCES

48" CUT @ 48.5" +/- 0.24"

*THICKNESS

Standard:

.134" (3.4MM) TO .472" (12MM)

*LENGTH

Standard:

25 FT. (7.62M) & 50 FT. (15.24M)

COLORED EPDM GRANULATE

0.0394" (1MM) TO 0.1181" (3MM)

BINDER

URETHANE

TOLERANCE

+/- 0.020"

The color concentration of the standard rolls and tiles is 20%.

*CUSTOM AVAILABLE * 3 FT. (.91M) AVAILABLE AS CUSTOM WIDTH



ULTIMATE TOUGH SPECIFICATIONS

TEST TYPE	ASTM	COLOR	BLACK
SHORE HARDNESS	D-2240	60 +/- 5	60 +/- 5
DENSITY	D-792	65 LBS./CU.FT.	60 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	100%	85-125%
TENSILE STRENGTH	D-412	250 PSI	250 PSI
TABER ABRASION	D-3884	0.47	0.45
COMPRESSION SET	D-395	8.4%	< 12%
VOC EMISSIONS	D-5116	0.5 MG/M ² OR LESS	0.5 MG/M ² OR LESS
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE	NO CHANGE
STATIC LOAD LIMIT	F-970	-0.001 IN	-0.001 IN
ELECTROSTATIC PROPENSITY	AATCC 134-1996	NEG 0.4 KV	----
DIE- C TEAR	D-624	70 LB/IN	95 PPI
COEFFICIENT OF FRICTION	D-1894-95	----	WET 1.2 DRY 1.2

NOTE:

Physical properties can vary by product type.
Information above applies to this product only.

STANDARD COLORS



NO. 106
BLACK




NO. 125
GREY




NO. 109
RED



NO. 122
BLUE/GREY



NO. 126
GREEN



NO. 127
BLUE



NO. 177
COCOA/EGGSHELL

MAINTENANCE & FLOOR CARE

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com

WARRANTY

Ultimate Tough Rolls and Tiles carry a 1-year limited lifetime warranty for defects in material and workmanship.

